



**NEW**  
**12 - 264 V**



**Explosionsgeschützte  
LED Handleuchte**  
**Baladeuse antidéflagrante LED**  
**Explosionproof LED Hand Lamp**

**Technische Daten / Caractéristiques techniques / Technical Data**

Kennzeichnung nach 94/9/E  II 2G  
*Marquage selon 94/9/CE*  II 2D  
Marking to 94/9/EC

Zündschutzart (Gas)  
*Mode de protection* Ex d IIC T5 Gb  
Type of protection

Zündschutzart (Staub)  
*Mode de protection* Ex t IIIC T95°C Db  
Type of protection

EG-Baumusterprüfbescheinigung  
*Certificat CE Examen de type* BVS 07 ATEX E 164 X  
EC Type Examination Certificate

Internationale Zulassungen  
*Certification internationale* IECEx BVS 08.0014 X  
International certifications

Schutzart nach EN 60529  
*Mode de protection selon EN 60529* IP 68 (2.5 m for 24 hours)  
Protection degree to EN 60529

Gehäusematerial  
*Matière de l'enveloppe* Polycarbonat / Aluminium  
Enclosure material Polycarbonate / aluminium  
Polycarbonate / aluminium

Standard Kabellänge  
*Longueur standard du câble* 5 m Kabel 3 · 1 mm<sup>2</sup> ohne Stecker  
Standard cable length 5 m câble 3 · 1 mm<sup>2</sup> sans fiche  
5 m cable 3 · 1 mm<sup>2</sup> without plug

Spannungen  
*Tension* 12-24 VDC (only)  
Voltage 24-50 VAC/DC (50-400 Hz)  
85-264 VAC (50-400 Hz)  
120-370 VDC

Zulässige Umgebungstemperatur  
*Température ambiante admise* -20°C bis/à/to 60°C  
Admissible ambient temperature

\* Mehrpreis: Änderung der Kabellänge oder Stecker inkl. Montage.  
*Suppl. de prix: autre longueur de câble ou fiche Ex (montage inclus).*  
Price add-ons: change to cable length or Ex plug including assembly.

